# Henry.

## SAFETY DATA SHEET

Issue Date 20-Dec-2015

Revision Date 28-Dec-2016

Version 1

#### **1. IDENTIFICATION**

Product identifier Product Name

BAKOR HI-TAC ADHESIVE

Other means of identificationProduct CodeBK103UN/ID noUN1133SynonymsNone

Recommended use of the chemical and restrictions on useRecommended UseAdhesives and/or sealantsUses advised againstNo information available

Details of the supplier of the safety data sheet Manufacturer Address HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Web Site: www.henry.com www.ca.henry.com

#### Emergency telephone number Company Phone Number Emergency Telephone

800-486-1278 CHEMTREC: 800-424-9300 CHEMTREC: 703-527-3887 CANUTEC: 613-966-6666

#### 2. HAZARDS IDENTIFICATION

#### **Classification**

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Skin corrosion/irritation                          | Category 2  |
|--|-------------|
| Serious eye damage/eye irritation                  | Category 2A |
| Reproductive toxicity                              | Category 2  |
| Specific target organ toxicity (single exposure)   | Category 3  |
| Specific target organ toxicity (repeated exposure) | Category 2  |
| Flammable liquids                                  | Category 2  |

#### Label elements

#### **Emergency Overview**

Danger

Hazard statements Causes skin irritation Causes serious eye irritation Suspected of damaging fertility or the unborn child May cause respiratory irritation. May cause drowsiness or dizziness May cause damage to organs through prolonged or repeated exposure Highly flammable liquid and vapor



Appearance viscous

Physical state liquid

Odor Petroleum distillates

#### **Precautionary Statements - Prevention**

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating / lighting/ mixing / equipment Use only non-sparking tools Take precautionary measures against static discharge

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention If skin irritation occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up Store in a well-ventilated place. Keep container tightly closed Keep cool

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

Not applicable

#### Other Information

May be harmful in contact with skin. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

#### Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substance

Not applicable

#### <u>Mixture</u>

| Chemical Name      | CAS No    | Weight-% |
|--------------------|-----------|----------|
| Stoddard solvent * | 8052-41-3 | 15 - 40  |

| Petroleum distillates, hydrotreated light * | 64742-47-8  | 10 - 30 |
|---|-------------|---------|
| Rubber Compounds *                          | Proprietary | 10 - 30 |
| Toluene *                                   | 108-88-3    | 1 - 5   |
| 1,2,4-Trimethylbenzene *                    | 95-63-3     | 1 - 5   |

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

#### 4. FIRST AID MEASURES

| Description of first aid measures  |  |  |
|--|--|--|
| General advice   | In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.  |  |
| Eye contact  | Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.            |  |
| Skin contact   | Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician. Wash contaminated clothing before reuse.  |  |
| Inhalation   | Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration.<br>Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If<br>symptoms persist, call a physician. |  |
| Ingestion  | Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.  |  |
| Self-protection of the first aider   | Remove all sources of ignition. Use personal protective equipment as required.   |  |
| Most important symptoms and effe   | ects, both acute and delayed   |  |
| Symptoms   | May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Drowsiness. Dizziness.  |  |
| Indication of any immediate medical attention and special treatment needed |  |  |
| Note to physicians   | Treat symptomatically.   |  |
|  | 5. FIRE-FIGHTING MEASURES  |  |

#### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO2, sand, earth, water spray or regular foam.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

#### Specific hazards arising from the chemical

Flash back possible over considerable distance. Flammable/toxic gases may accumulate in confined areas (basements, tanks, hopper/tank cars etc.). Most vapors are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks). Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge May be ignited by heat, sparks or flames.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

| Personal precautions  | Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required. Keep people away from and upwind of spill/leak.  |  |
|---|--|--|
| For emergency responders  | Be aware that gases can spread at ground level (heavier than air) and pay attention to the wind direction. Pay attention to flashback. Remove all sources of ignition. Use personal protective equipment as required.  |  |
| Environmental precautions                                       |  |  |
| Environmental precautions                                       | Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.  |  |
| Methods and material for containm                               | ent and cleaning up  |  |
| Methods for containment   | Prevent further leakage or spillage if safe to do so.  |  |
| Methods for cleaning up   | Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.  |  |
|   | containers.  |  |
|   | 7. HANDLING AND STORAGE  |  |
| Precautions for safe handling                                   |  |  |
| <u>Precautions for safe handling</u><br>Advice on safe handling |  |  |
|   | 7. HANDLING AND STORAGE<br>Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. |  |
| Advice on safe handling   | 7. HANDLING AND STORAGE<br>Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. |  |

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

#### Exposure Guidelines

| Chemical Name                     | ACGIH TLV                            | OSHA PEL                                    | NIOSH IDLH  |
|-----------------------------------|--------------------------------------|---|---|
| Stoddard solvent<br>8052-41-3     | TWA: 100 ppm                         | TWA: 500 ppm<br>TWA: 2900 mg/m <sup>3</sup> | IDLH: 20000 mg/m <sup>3</sup><br>Ceiling: 1800 mg/m <sup>3</sup> 15 min<br>TWA: 350 mg/m <sup>3</sup>       |
| Toluene<br>108-88-3               | TWA: 20 ppm                          | TWA: 200 ppm<br>Ceiling: 300 ppm            | IDLH: 500 ppm<br>TWA: 100 ppm<br>TWA: 375 mg/m <sup>3</sup><br>STEL: 150 ppm<br>STEL: 560 mg/m <sup>3</sup> |
| 1,2,4-Trimethylbenzene<br>95-63-3 | TWA: 25 ppm<br>123 mg/m <sup>3</sup> | TWA: 25 ppm<br>120 mg/m <sup>3</sup>        | TWA: 25 ppm   |

NIOSH IDLH Immediately Dangerous to Life or Health

#### Appropriate engineering controls

Engineering Controls

Showers Eyewash stations

.

Ventilation systems.

#### Individual protection measures, such as personal protective equipment

| Eye/face protection            | Wear safety glasses with side shields (or goggles).   |
|--------------------------------|---|
| Skin and body protection       | Wear protective gloves and protective clothing.   |
| Respiratory protection         | If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations. |
| General Hygiene Considerations | Handle in accordance with good industrial hygiene and safety practice.  |

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

| Physical state<br>Appearance<br>Color   | liquid<br>viscous<br>yellow   | Odor<br>Odor threshold | Petroleum distillates<br>No information available |
|---|---|------------------------|---|
| Property<br>pH<br>Melting point / freezing point<br>Boiling point / boiling range<br>Flash point<br>Evaporation rate  | Values_<br>No information available<br>No information available<br>97 °C / 207 °F<br>-4 °C / 25 °F<br>No information available  | Remarks • Method       |   |
| Flammability (solid, gas)<br>Flammability Limit in Air<br>Upper flammability limit:<br>Lower flammability limit:<br>Vapor pressure<br>Vapor density<br>Relative density<br>Water solubility<br>Solubility in other solvents<br>Partition coefficient<br>Autoignition temperature<br>Decomposition temperature<br>Kinematic viscosity<br>Dynamic viscosity<br>Explosive properties<br>Oxidizing properties | No information available<br>7.4%<br>1.4%<br>No information available<br>No information available<br>0.8-0.85<br>Insoluble in water<br>No information available<br>223 °C / 433 °F<br>No information available<br>>100 mm2/s<br>No information available<br>Not an explosive<br>Not applicable | @ 40 °C                |   |
| Other Information<br>Softening point<br>Molecular weight<br>VOC Content (%)<br>Density<br>Bulk density  | No information available<br>No information available<br>No information available<br>No information available<br>No information available  |                        |   |

#### **10. STABILITY AND REACTIVITY**

Reactivity No data available

Chemical stability

Stable under recommended storage conditions. Possibility of Hazardous Reactions None under normal processing. <u>Conditions to avoid</u> Heat, flames and sparks. Incompatible materials. <u>Incompatible materials</u> Strong oxidizing agents. Strong acids. Strong bases. <u>Hazardous Decomposition Products</u> Thermal decomposition can lead to release of irritating and toxic gases and vapors.

#### **11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

#### **Product Information**

| Inhalation   | May cause irritation of respiratory tract. May cause drowsiness or dizziness. |
|--------------|---|
| Eye contact  | Irritating to eyes.   |
| Skin contact | Irritating to skin.   |

Ingestion

Based on available data, the classification criteria are not met.

| Chemical Name  | Oral LD50          | Dermal LD50            | Inhalation LC50      |
|--|--------------------|------------------------|----------------------|
| Petroleum distillates, hydrotreated<br>light<br>64742-47-8 | > 5000 mg/kg (Rat) | > 2000 mg/kg (Rabbit)  | > 5.2 mg/L (Rat)4 h  |
| Toluene<br>108-88-3  | = 2600 mg/kg (Rat) | = 12000 mg/kg (Rabbit) | = 12.5 mg/L (Rat)4 h |

#### Information on toxicological effects

#### Symptoms

May cause redness and tearing of the eyes. May cause skin irritation. Vapors may cause drowsiness and dizziness. Coughing and/ or wheezing.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

| Sensitization                 | Based on available data, the classification criteria are not met.                        |  |                                       |      |
|-------------------------------|--|--|---------------------------------------|------|
| Germ cell mutagenicity        | Based on available data, the classification criteria are not met.                        |  |                                       |      |
| Carcinogenicity               | The table belo   | The table below indicates whether each agency has listed any ingredient as a carcinogen. |                                       |      |
| Chemical Name                 | ACGIH  | IARC   | NTP                                   | OSHA |
| Toluene                       | -  | Group 3  | -                                     | -    |
| 108-88-3                      |  | -  |                                       |      |
| IARC (International Agency    | for Research on Cancer   |  | · · · · · · · · · · · · · · · · · · · |      |
| Not classifiable as a human c | arcinogen  |  |                                       |      |
| Reproductive toxicity         | Contains a kno   | own or suspected reproc  | luctive toxin.                        |      |
| STOT - single exposure        | Target Organs. Respiratory system.   |  |                                       |      |
| STOT - repeated exposure      | May cause dis  | May cause disorder and damage to the. Central nervous system.                            |                                       |      |
| Chronic toxicity              | May cause ad   | May cause adverse liver effects.   |                                       |      |
| Target Organ Effects          | Respiratory system, Eyes, Skin, Central nervous system, kidney, liver.                   |  |                                       |      |
| Neurological effects          | Intentional misuse by deliberately concentrating and inhaling contents may be harmful or |  |                                       |      |
| C C                           | fatal.   |  |                                       |      |
| Aspiration hazard             | Based on available data, the classification criteria are not met.                        |  |                                       |      |
| Numerical measures of toxic   | city - Product Informa   | tion   |                                       |      |
| The following values are cal  | culated based on chap  | oter 3.1 of the GHS doo  | cument .                              |      |
| ATEmix (oral)                 | 5,183.00 mg/kg   |  |                                       |      |
| ATEmix (dermal)               | 3,600.00 mg/kg   |  |                                       |      |
| • <b></b> • • • • • • • •     |  |  |                                       |      |

## ATEmix (inhalation-gas)3,148,048.14 mg/lATEmix (inhalation-dust/mist)15.00 mg/kg mg/l

#### **12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

Harmful to aquatic life with long lasting effects

10 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

#### Persistence and degradability

Not readily biodegradable.

#### **Bioaccumulation**

| Chemical Name | Partition coefficient |
|---------------|-----------------------|
| Toluene       | 2.65                  |
| 108-88-3      |                       |

#### Other adverse effects

No information available

| 13. DISPOSAL CONSIDERATIONS                          |   |  |  |
|--|---|--|--|
| <u>Waste treatment methods</u><br>Disposal of wastes | This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261). Dispose of in accordance with federal, state and local regulations. |  |  |
| Contaminated packaging                               | Disposal should be in accordance with applicable regional, national and local laws and regulations. Do not reuse container.   |  |  |
| US EPA Waste Number                                  | D001  |  |  |

| Chemical Name       | RCRA - Halogenated<br>Organic Compounds | RCRA - P Series Wastes | RCRA - F Series Wastes   | RCRA - K Series Wastes |
|---------------------|---|------------------------|--|------------------------|
| Toluene<br>108-88-3 | -                                       | -                      | Toxic waste<br>waste number F025<br>Waste description:<br>Condensed light ends, spent<br>filters and filter aids, and<br>spent desiccant wastes from<br>the production of certain<br>chlorinated aliphatic<br>hydrocarbons, by free<br>radical catalyzed processes.<br>These chlorinated aliphatic | -                      |
|                     |   |                        | hydrocarbons are those<br>having carbon chain lengths<br>ranging from one to and<br>including five, with varying<br>amounts and positions of<br>chlorine substitution.   |                        |

| Chemical Name | California Hazardous Waste Status |
|---------------|-----------------------------------|
| Toluene       | Toxic                             |
| 108-88-3      | Ignitable                         |

#### **14. TRANSPORT INFORMATION**

DOT

| UN1133                           |
|----------------------------------|
| Adhesives                        |
| 3                                |
| II                               |
| 149, B52, IB2, T4, TP1, TP8      |
| UN1133, Adhesives mixture, 3, II |
|                                  |

Emergency Response Guide 128 Number

#### TDG

| UN/ID no<br>Proper shipping name<br>Hazard Class<br>Packing Group | UN1133<br>Adhesives mixture<br>3<br>II |
|---|--|
| Description   | UN1133, Adhesives mixture, 3, II       |
| ΙΑΤΑ  |  |
| UN/ID no  | UN1133                                 |
| Proper shipping name  | Adhesives                              |
| Hazard Class  | 3                                      |
| Packing Group   | II                                     |
| ERG Code  | 3L                                     |
| Special Provisions  | A3                                     |
| Description   | UN1133, Adhesives, 3, II               |
| IMDG  |  |
| UN/ID no  | UN1133                                 |
| Proper shipping name  | Adhesives                              |
| Hazard Class  | 3                                      |

II F-E, S-D

#### **15. REGULATORY INFORMATION**

UN1133, Adhesives, 3, II (-4°C c.c.)

All components used in this product are on the TSCA Inventory and the Canadian DSL.

#### International Inventories

**Packing Group** 

EmS-No Description

| TSCA          | Complies |
|---------------|----------|
| DSL/NDSL      | Complies |
| EINECS/ELINCS | Complies |
| IECSC         | Complies |
| KECL          | Complies |
| PICCS         | Complies |
| AICS          | Complies |

Legend:

 TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

 ENCS - Japan Existing and New Chemical Substances

 IECSC - China Inventory of Existing Chemical Substances

 KECL - Korean Existing and Evaluated Chemical Substances

 PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### US Federal Regulations

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name                     | SARA 313 - Threshold Values % |
|-----------------------------------|-------------------------------|
| Toluene - 108-88-3                | 1.0                           |
| SARA 311/312 Hazard Categories    |                               |
| Acute health hazard               | Yes                           |
| Chronic Health Hazard             | Yes                           |
| Fire hazard                       | Yes                           |
| Sudden release of pressure hazard | No                            |

#### Reactive Hazard

No

#### CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

| Chemical Name | CWA - Reportable<br>Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous<br>Substances |
|---------------|--------------------------------|------------------------|---------------------------|-------------------------------|
| Toluene       | 1000 lb                        | Х                      | Х                         | Х                             |
| 108-88-3      |                                |                        |                           |                               |

#### CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

| Chemical Name | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ)         |
|---------------|--------------------------|----------------|----------------------------------|
| Toluene       | 1000 lb 1 lb             | -              | RQ 1000 lb final RQ              |
| 108-88-3      |                          |                | RQ 454 kg final RQ RQ 1 lb final |
|               |                          |                | RQ                               |
|               |                          |                | RQ 0.454 kg final RQ             |

#### US State Regulations

#### California Proposition 65

This product contains the following Proposition 65 chemicals

| Chemical Name      | California Proposition 65 |  |  |
|--------------------|---------------------------|--|--|
| Toluene - 108-88-3 | Developmental             |  |  |
|                    |                           |  |  |

#### U.S. State Right-to-Know Regulations

| Chemical Name                             | New Jersey | Massachusetts | Pennsylvania |
|---|------------|---------------|--------------|
| Stoddard solvent<br>8052-41-3             | Х          | Х             | Х            |
| Toluene<br>108-88-3                       | Х          | Х             | Х            |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | Х          | Х             | Х            |
| Triphenyl phosphate<br>115-86-6           | Х          | Х             | Х            |

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

#### 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

| <u>NFPA</u>                      | Health hazards 2                   | Flammability 3                  | Instability 0      | Physical and Chemical<br>Properties - |
|----------------------------------|------------------------------------|---------------------------------|--------------------|---------------------------------------|
| HMIS<br>Chronic Hazard Star Lege | Health hazards 2*<br>nd *= Chronic | Flammability 3<br>Health Hazard | Physical hazards 0 | Personal protection X                 |
| 0                                |                                    |                                 |                    |                                       |

Issue Date20-Dec-2015Revision Date28-Dec-2016Revision Note28-Dec-2016No information available100 model

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

#### End of Safety Data Sheet