



# SAFETY DATA SHEET

Issue Date 08-Dec-2015

Revision Date 15-Feb-2016

Version 1

## 1. IDENTIFICATION

### Product identifier

**Product Name** BAKOR CLEARPATCH ROOF SEALANT

### Other means of identification

**Product Code** BK212  
**UN/ID no** UN1133  
**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Sealant  
**Uses advised against** No information available

### Details of the supplier of the safety data sheet

**Manufacturer Address**  
HENRY COMPANY  
999 N. Sepulveda Blvd., Suite 800  
El Segundo, CA 90245-2716  
Web Site: [www.henry.com](http://www.henry.com) [www.ca.henry.com](http://www.ca.henry.com)

### Emergency telephone number

**Company Phone Number** 800-486-1278  
**Emergency Telephone** CHEMTREC: 800-424-9300  
CHEMTREC: 703-527-3887  
CANUTEC: 613-966-6666

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

### Label elements

#### **Emergency Overview**

#### **Warning**

#### **Hazard statements**

Causes skin irritation  
Causes serious eye irritation  
May cause respiratory irritation. May cause drowsiness or dizziness  
Flammable liquid and vapor

**Appearance** viscous**Physical state** liquid**Odor** Aromatic Petroleum distillates**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
 Wear protective gloves/protective clothing/eye protection/face protection  
 Avoid breathing dust/fume/gas/mist/vapors/spray  
 Use only outdoors or in a well-ventilated area  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
 Keep container tightly closed  
 Ground/bond container and receiving equipment  
 Use explosion-proof electrical/ ventilating/ lighting/ equipment  
 Use only non-sparking tools  
 Take precautionary measures against static discharge

**Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 If eye irritation persists: Get medical advice/attention  
 If skin irritation occurs: Get medical advice/attention  
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
 Wash contaminated clothing before reuse  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 Call a POISON CENTER or doctor/physician if you feel unwell  
 In case of fire: Use CO<sub>2</sub>, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed  
 Store locked up  
 Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

May be harmful if swallowed. May be harmful in contact with skin. Very toxic to aquatic life with long lasting effects. Very toxic to aquatic life.

**Unknown acute toxicity**

46.0661914% of the mixture consists of ingredient(s) of unknown toxicity

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

**Substance**

Not applicable

**Mixture**

Chemical Name	CAS No	Weight-%
---------------	--------	----------

Xylenes (o-, m-, p- isomers) *	1330-20-7	15 - 40
Hydrocarbon resins *	Proprietary	10 - 30
Rubber compounds *	Proprietary	10 - 30
Paraffin oils *	8012-95-1	10 - 30
Silica, amorphous, fumed, crystalline-free *	112945-52-5	1 - 5

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

#### 4. FIRST AID MEASURES

##### Description of first aid measures

<b>General advice</b>	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.
<b>Eye contact</b>	Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.
<b>Skin contact</b>	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician. Wash contaminated clothing before reuse.
<b>Inhalation</b>	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.
<b>Ingestion</b>	Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.
<b>Self-protection of the first aider</b>	Remove all sources of ignition. Use personal protective equipment as required.

##### Most important symptoms and effects, both acute and delayed

<b>Symptoms</b>	May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Drowsiness.
-----------------	--

##### Indication of any immediate medical attention and special treatment needed

<b>Note to physicians</b>	Keep victim warm and quiet.
---------------------------	-----------------------------

#### 5. FIRE-FIGHTING MEASURES

##### Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO<sub>2</sub>, sand, earth, water spray or regular foam.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

##### Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors form explosive mixtures with air: indoors, outdoors, and sewers explosion hazards.

##### Explosion data

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

##### Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

- Personal precautions** ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.
- Other Information** Water spray may reduce vapor; but may not prevent ignition in closed spaces.

### Environmental precautions

- Environmental precautions** Prevent entry into waterways, sewers, basements or confined areas.

### Methods and material for containment and cleaning up

- Methods for containment** A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
- Methods for cleaning up** Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.

## 7. HANDLING AND STORAGE

### Precautions for safe handling

- Advice on safe handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray.

### Conditions for safe storage, including any incompatibilities

- Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.
- Incompatible materials** Strong oxidizing agents. Strong acids. Strong bases.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylenes (o-, m-, p- isomers) 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m <sup>3</sup>	-
Paraffin oils 8012-95-1	TWA: 5 mg/m <sup>3</sup> inhalable fraction excluding metal working fluids, highly & severely refined TWA: 5 mg/m <sup>3</sup> inhalable fraction excluding metal working fluids	TWA: 5 mg/m <sup>3</sup>	IDLH: 2500 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>

NIOSH IDLH *Immediately Dangerous to Life or Health*

### Appropriate engineering controls

- Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin and body protection</b>	Wear protective gloves and protective clothing.
<b>Respiratory protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
<b>General Hygiene Considerations</b>	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES****Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Aromatic Petroleum distillates
<b>Appearance</b>	viscous	<b>Odor threshold</b>	No information available
<b>Color</b>	clear	<b>Remarks • Method</b>	
<b>Property</b>	<b>Values</b>		
<b>pH</b>	No information available		
<b>Melting point / freezing point</b>	No information available		
<b>Boiling point / boiling range</b>	150 °C / 302 °F		
<b>Flash point</b>	24 °C / 75 °F		Pensky-Martens Closed Cup (PMCC)
<b>Evaporation rate</b>	No information available		
<b>Flammability (solid, gas)</b>	No information available		
<b>Flammability Limit in Air</b>			
<b>Upper flammability limit:</b>	9%		
<b>Lower flammability limit:</b>	1%		
<b>Vapor pressure</b>	No information available		
<b>Vapor density</b>	No information available		
<b>Relative density</b>	0.9 - 1.3		
<b>Water solubility</b>	Insoluble in water		
<b>Solubility in other solvents</b>	No information available		
<b>Partition coefficient</b>	No information available		
<b>Autoignition temperature</b>	No information available		
<b>Decomposition temperature</b>	No information available		
<b>Kinematic viscosity</b>	>100 mm <sup>2</sup> /s		@ 40 °C
<b>Dynamic viscosity</b>	No information available		
<b>Explosive properties</b>	No information available		
<b>Oxidizing properties</b>	No information available		
<b>Other Information</b>			
<b>Softening point</b>	No information available		
<b>Molecular weight</b>	No information available		
<b>VOC Content (%)</b>	No information available		
<b>Density</b>	No information available		
<b>Bulk density</b>	No information available		

**10. STABILITY AND REACTIVITY****Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks. Incompatible materials.

**Incompatible materials**

Strong oxidizing agents. Strong acids. Strong bases.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

**11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Product Information**

<b>Inhalation</b>	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg ( Rat )	> 4350 mg/kg ( Rabbit ) > 1700 mg/kg ( Rabbit )	= 29.08 mg/L ( Rat ) 4 h = 5000 ppm ( Rat ) 4 h
Paraffin oils 8012-95-1	> 24 g/kg ( Rat )	-	= 2062 ppm ( Rat ) 4 h
Silica, amorphous, fumed, crystalline-free 112945-52-5	= 3160 mg/kg ( Rat )	-	-

**Information on toxicological effects**

**Symptoms** May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Vapors may cause drowsiness and dizziness.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen. The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3	-	-
Paraffin oils 8012-95-1	A2	Group 1 Group 3	-	X
Silica, amorphous, fumed, crystalline-free 112945-52-5	-	Group 3	-	-

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinogen

Group 1 - Carcinogenic to Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

**Reproductive toxicity** No information available.  
**STOT - single exposure** Target Organs. Respiratory system. Central nervous system. Eyes. Skin.  
**STOT - repeated exposure** No information available.

<b>Chronic toxicity</b>	Avoid repeated exposure.
<b>Target Organ Effects</b>	Eyes, Respiratory system, Skin.
<b>Aspiration hazard</b>	No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

<b>ATEmix (oral)</b>	3,800.00 mg/kg
<b>ATEmix (dermal)</b>	2,681.90 mg/kg
<b>ATEmix (inhalation-dust/mist)</b>	2.36 mg/l

## 12. ECOLOGICAL INFORMATION

**Ecotoxicity**

Toxic to aquatic life with long lasting effects

51.0626 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Xylenes (o-, m-, p- isomers) 1330-20-7	-	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 19: 96 h Lepomis macrochirus mg/L LC50	3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
White mineral oil, petroleum 8042-47-5	-	10000: 96 h Lepomis macrochirus mg/L LC50	-
Ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	1.8 - 2.4: 48 h Daphnia magna mg/L EC50

**Persistence and degradability**

Not readily biodegradable.

**Bioaccumulation**

Chemical Name	Partition coefficient
Xylenes (o-, m-, p- isomers) 1330-20-7	3.15

**Other adverse effects**

No information available

## 13. DISPOSAL CONSIDERATIONS

**Waste treatment methods**

**Disposal of wastes** This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Included in waste stream: F039	-	U239
Ethylbenzene 100-41-4	-	Included in waste stream: F039	-	-

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Xylenes (o-, m-, p- isomers) 1330-20-7	Toxic Ignitable

**14. TRANSPORT INFORMATION**

**DOT**

**UN/ID no** UN1133  
**Proper shipping name** Adhesives  
**Hazard Class** 3  
**Packing Group** III  
**Special Provisions** B1, B52, IB3, T2, TP1  
**Description** UN1133, Adhesives, 3, III  
**Emergency Response Guide Number** 128

**TDG**

**UN/ID no** UN1133  
**Proper shipping name** Adhesives  
**Hazard Class** 3  
**Packing Group** III  
**Description** UN1133, Adhesives, 3, III

**IATA**

**UN/ID no** UN1133  
**Proper shipping name** Adhesives  
**Hazard Class** 3  
**Packing Group** III  
**ERG Code** 3L  
**Special Provisions** A3  
**Description** UN1133, Adhesives, 3, III

**IMDG**

**UN/ID no** UN1133  
**Proper shipping name** Adhesives  
**Hazard Class** 3  
**Packing Group** III  
**EmS-No** F-E, S-D  
**Special Provisions** 223, 955  
**Description** UN1133, Adhesives, 3, III, (24°C c.c.)

**15. REGULATORY INFORMATION**

All components used in this product are on the TSCA Inventory and the Canadian DSL.



**International Inventories**

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

**Legend:**

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Xylenes (o-, m-, p- isomers) - 1330-20-7	1.0

**SARA 311/312 Hazard Categories**

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb	-	-	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ

**US State Regulations****California Proposition 65**

This product does not contain any Proposition 65 chemicals

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylenes (o-, m-, p- isomers) 1330-20-7	X	X	X
Paraffin oils 8012-95-1	X	X	X

**U.S. EPA Label Information**

EPA Pesticide Registration Number Not applicable

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<u>NFPA</u>	Health hazards 2	Flammability 3	Instability 0	Physical and Chemical Properties -
<u>HMIS</u>	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection X

Issue Date 08-Dec-2015

Revision Date 15-Feb-2016

**Revision Note**

No information available

**Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**