



# SAFETY DATA SHEET

Issue Date 21-Nov-2015

Revision Date 04-Nov-2015

Version 1

## 1. IDENTIFICATION

### Product identifier

**Product Name** BAKOR 810-14 HEAVY DUTY ASPHALT ROOF COATING

### Other means of identification

**Product Code** BK81014F

**Synonyms** None

### Recommended use of the chemical and restrictions on use

**Recommended Use** Coatings Sealant

**Uses advised against** No information available

### Details of the supplier of the safety data sheet

#### **Manufacturer Address**

HENRY COMPANY

999 N. Sepulveda Blvd., Suite 800

El Segundo, CA 90245-2716

Web Site: [www.henry.com](http://www.henry.com) [www.ca.henry.com](http://www.ca.henry.com)

### Emergency telephone number

**Company Phone Number** 800-486-1278

**Emergency Telephone** CHEMTREC: 800-424-9300

CHEMTREC: 703-527-3887

CANUTEC: 613-966-6666

## 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

### Label elements

#### **Emergency Overview**

#### **Warning**

#### **Hazard statements**

Causes skin irritation

Causes serious eye irritation

May cause respiratory irritation. May cause drowsiness or dizziness

Flammable liquid and vapor



**Appearance** viscous

**Physical state** liquid

**Odor** Solvent

**Precautionary Statements - Prevention**

Wash face, hands and any exposed skin thoroughly after handling  
Wear protective gloves/protective clothing/eye protection/face protection  
Avoid breathing dust/fume/gas/mist/vapors/spray  
Use only outdoors or in a well-ventilated area  
Keep away from heat/sparks/open flames/hot surfaces. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical/ ventilating / lighting/ mixing / equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge

**Precautionary Statements - Response**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
If skin irritation occurs: Get medical advice/attention  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower  
Wash contaminated clothing before reuse  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor/physician if you feel unwell  
In case of fire: Use CO2, dry chemical, or foam for extinction

**Precautionary Statements - Storage**

Store in a well-ventilated place. Keep container tightly closed  
Store locked up  
Keep cool

**Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

**Hazards not otherwise classified (HNOC)**

Not applicable

**Other Information**

May be harmful in contact with skin. Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

**Unknown acute toxicity**

24.67952% of the mixture consists of ingredient(s) of unknown toxicity

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

**Substance**

Not applicable

**Mixture**

Chemical Name	CAS No	Weight-%
Asphalt *	8052-42-4	15 - 40

Solvent naphtha, petroleum, medium aliphatic *	64742-88-7	15 - 40
Mica *	12001-26-2	10 - 30
Cellulose *	9004-34-6	3 - 7
Polymer Blend *	Proprietary	1 - 5
Fullers earth *	8031-18-3	1 - 5
Bentonite *	1302-78-9	1 - 5

\*The exact percentage (concentration) of composition has been withheld as a trade secret.

**4. FIRST AID MEASURES**

**Description of first aid measures**

- General advice** Immediate medical attention is required. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).
- Eye contact** Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.
- Skin contact** Wash off immediately with plenty of water.
- Inhalation** Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.
- Ingestion** Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.
- Self-protection of the first aider** Remove all sources of ignition.

**Most important symptoms and effects, both acute and delayed**

**Symptoms** May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Drowsiness. Dizziness.

**Indication of any immediate medical attention and special treatment needed**

**Note to physicians** Treat symptomatically.

**5. FIRE-FIGHTING MEASURES**

**Suitable extinguishing media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO2, sand, earth, water spray or regular foam.

**Unsuitable extinguishing media** Do not use a solid water stream as it may scatter and spread fire.

**Specific hazards arising from the chemical**

Flammable.

**Explosion data**

**Sensitivity to Mechanical Impact** None.

**Sensitivity to Static Discharge** None.

**Protective equipment and precautions for firefighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions, protective equipment and emergency procedures**

**Personal precautions** Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Use personal protective equipment as required.

**Environmental precautions**

**Environmental precautions** Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not flush into surface water or sanitary sewer system.

**Methods and material for containment and cleaning up**

**Methods for containment** Prevent further leakage or spillage if safe to do so.

**Methods for cleaning up** Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labeled containers.

**7. HANDLING AND STORAGE**

**Precautions for safe handling**

**Advice on safe handling** Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded.

**Conditions for safe storage, including any incompatibilities**

**Storage Conditions** Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity).

**Incompatible materials** Strong oxidizing agents. Strong acids. Strong bases.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Control parameters**

**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Asphalt 8052-42-4	TWA: 0.5 mg/m <sup>3</sup> benzene soluble aerosol fume, inhalable fraction	-	Ceiling: 5 mg/m <sup>3</sup> fume 15 min
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	-	TWA: 500 ppm TWA: 2900 mg/m <sup>3</sup>	-
Mica 12001-26-2	TWA: 3 mg/m <sup>3</sup> respirable fraction	TWA: 20 mppcf <1% Crystalline silica	IDLH: 1500 mg/m <sup>3</sup> TWA: 3 mg/m <sup>3</sup> containing <1% Quartz respirable dust
Cellulose 9004-34-6	TWA: 10 mg/m <sup>3</sup>	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable dust TWA: 1 mg/m <sup>3</sup>
Bentonite 1302-78-9	TWA: 1 mg/m <sup>3</sup> respirable fraction	-	-

*NIOSH IDLH Immediately Dangerous to Life or Health*

**Appropriate engineering controls**

**Engineering Controls** Showers  
Eyewash stations  
Ventilation systems.

**Individual protection measures, such as personal protective equipment**

<b>Eye/face protection</b>	Wear safety glasses with side shields (or goggles).
<b>Skin and body protection</b>	Wear protective gloves and protective clothing.
<b>Respiratory protection</b>	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
<b>General Hygiene Considerations</b>	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Information on basic physical and chemical properties**

<b>Physical state</b>	liquid	<b>Odor</b>	Solvent
<b>Appearance</b>	viscous	<b>Odor threshold</b>	No information available
<b>Color</b>	black		
<b>Property</b>	<b>Values</b>	<b>Remarks • Method</b>	
<b>pH</b>	No information available		
<b>Melting point / freezing point</b>	No information available		
<b>Boiling point / boiling range</b>	> 150 °C / 302 °F		
<b>Flash point</b>	42 °C / 108 °F	Pensky-Martens Closed Cup (PMCC)	
<b>Evaporation rate</b>	No information available		
<b>Flammability (solid, gas)</b>	No information available		
<b>Flammability Limit in Air</b>			
<b>Upper flammability limit:</b>	6		
<b>Lower flammability limit:</b>	1		
<b>Vapor pressure</b>	No information available		
<b>Vapor density</b>	3.6		
<b>Relative density</b>	1 - 1.1		
<b>Water solubility</b>	Insoluble in water		
<b>Solubility in other solvents</b>	No information available		
<b>Partition coefficient</b>	No information available		
<b>Autoignition temperature</b>	>250 °C / 482 °F		
<b>Decomposition temperature</b>	No information available		
<b>Kinematic viscosity</b>	> 100 mm <sup>2</sup> /s	@ 40 °C	
<b>Dynamic viscosity</b>	No information available		
<b>Explosive properties</b>	Not an explosive		
<b>Oxidizing properties</b>	Not applicable		

**Other Information**

<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC Content (%)</b>	No information available
<b>Density</b>	No information available
<b>Bulk density</b>	No information available

**10. STABILITY AND REACTIVITY**

**Reactivity**

No data available

**Chemical stability**

Stable under recommended storage conditions.

**Possibility of Hazardous Reactions**

None under normal processing.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible materials**

Strong oxidizing agents. Strong acids. Strong bases.

**Hazardous Decomposition Products**

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

**11. TOXICOLOGICAL INFORMATION**

**Information on likely routes of exposure**

**Product Information**

<b>Inhalation</b>	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
<b>Eye contact</b>	Irritating to eyes.
<b>Skin contact</b>	Irritating to skin.
<b>Ingestion</b>	No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Asphalt 8052-42-4	> 5000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	-
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	> 5000 mg/kg ( Rat )	= 3000 mg/kg ( Rabbit )	> 5.28 mg/L ( Rat ) 4 h
Cellulose 9004-34-6	> 5 g/kg ( Rat )	> 2 g/kg ( Rabbit )	> 5800 mg/m <sup>3</sup> ( Rat ) 4 h
Bentonite 1302-78-9	> 5000 mg/kg ( Rat )	-	-

**Information on toxicological effects**

**Symptoms** May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Vapors may cause drowsiness and dizziness.

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization** No information available.  
**Germ cell mutagenicity** No information available.  
**Carcinogenicity** The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Asphalt 8052-42-4	-	Group 2B	-	X
Cellulose 9004-34-6	-	Group 1	Known	X
Polymer Blend	-	Group 3	-	-

*IARC (International Agency for Research on Cancer)  
 Group 1 - Carcinogenic to Humans  
 Group 2B - Possibly Carcinogenic to Humans  
 Not classifiable as a human carcinogen  
 NTP (National Toxicology Program)  
 Known - Known Carcinogen  
 Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen  
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)  
 X - Present*

**Reproductive toxicity** No information available.  
**STOT - single exposure** Target Organs. Respiratory system. Eyes. Skin. Central nervous system.  
**STOT - repeated exposure** No information available.  
**Chronic toxicity** May cause adverse effects on the bone marrow and blood-forming system.  
**Target Organ Effects** Eyes, Respiratory system, Skin, blood, Central nervous system.

**Aspiration hazard** No information available.

**Numerical measures of toxicity - Product Information**

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 5,252.00 mg/kg  
 ATEmix (dermal) 2,573.00 mg/kg  
 ATEmix (inhalation-dust/mist) 67.40 mg/l

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

Harmful to aquatic life with long lasting effects

65.68642 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

**Persistence and degradability**

No information available.

**Bioaccumulation**

Chemical Name	Partition coefficient
Asphalt 8052-42-4	6

**Other adverse effects**

No information available

**13. DISPOSAL CONSIDERATIONS**

**Waste treatment methods**

**Disposal of wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.

**Contaminated packaging** Do not reuse container.

**US EPA Waste Number** D001

**14. TRANSPORT INFORMATION**

**DOT** Not regulated (If shipped in NON BULK packaging by ground transport)

**TDG** Not regulated (If shipped in NON BULK packaging by ground transport)

**IATA**

UN/ID no UN1999  
 Proper shipping name Tars, liquid  
 Hazard Class 3  
 Packing Group III  
 ERG Code 3L  
 Special Provisions A3  
 Description UN1999, Tars, liquid, 3, III

**IMDG**

Non-regulated per 2.3.2.5  
 UN/ID no UN1999  
 Proper shipping name Tars, liquid

<b>Hazard Class</b>	3
<b>Packing Group</b>	III
<b>EmS-No</b>	F-E, S-E
<b>Special Provisions</b>	955
<b>Description</b>	UN1999, Tars, liquid, 3, III, (42°C c.c.)

**15. REGULATORY INFORMATION**

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>IECSC</b>	Complies
<b>KECL</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory  
**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List  
**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances  
**ENCS** - Japan Existing and New Chemical Substances  
**IECSC** - China Inventory of Existing Chemical Substances  
**KECL** - Korean Existing and Evaluated Chemical Substances  
**PICCS** - Philippines Inventory of Chemicals and Chemical Substances  
**AICS** - Australian Inventory of Chemical Substances

**US Federal Regulations**

**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

**SARA 311/312 Hazard Categories**

<b>Acute health hazard</b>	Yes
<b>Chronic Health Hazard</b>	No
<b>Fire hazard</b>	Yes
<b>Sudden release of pressure hazard</b>	No
<b>Reactive Hazard</b>	No

**CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA**

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

**US State Regulations**

**California Proposition 65**

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Cellulose - 9004-34-6	Carcinogen
Quartz - 14808-60-7	Carcinogen

**U.S. State Right-to-Know Regulations**

Chemical Name	New Jersey	Massachusetts	Pennsylvania



Asphalt 8052-42-4	X	X	X
Solvent naphtha, petroleum, medium aliphatic 64742-88-7	X	-	-
Mica 12001-26-2	X	X	X
Cellulose 9004-34-6	X	X	X
Water 7732-18-5	-	-	X
Benzene, 1,2,4-trimethyl- 95-63-6	X	X	X
Quartz 14808-60-7	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 2	<b>Instability</b> 0	<b>Physical and Chemical Properties</b> -
<b>HMIS</b>	<b>Health hazards</b> 2	<b>Flammability</b> 2	<b>Physical hazards</b> 0	<b>Personal protection</b> X

**Issue Date** 21-Nov-2015  
**Revision Date** 04-Nov-2015

**Revision Note**  
No information available

**Disclaimer**

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**