Henry.

SAFETY DATA SHEET

Issue Date 16-Dec-2015

Revision Date 16-Dec-2015

Version 1

1. IDENTIFICATION

Product identifier Product Name

KOP-R-LASTIC ALUMINUMSTON

Other means of identificationProduct CodeKL310ASUN/ID noUN1133SynonymsNone

Recommended use of the chemical and restrictions on useRecommended UseSealantUses advised againstNo information available

Details of the supplier of the safety data sheet Manufacturer Address HENRY COMPANY 999 N. Sepulveda Blvd., Suite 800 El Segundo, CA 90245-2716 Web Site: www.henry.com www.ca.henry.com

Emergency telephone number Company Phone Number Emergency Telephone

800-486-1278 CHEMTREC: 800-424-9300 CHEMTREC: 703-527-3887 CANUTEC: 613-966-6666

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Flammable liquids	Category 3

Label elements

Emergency Overview

Warning

Hazard statements Causes skin irritation Causes serious eye irritation May cause respiratory irritation. May cause drowsiness or dizziness Flammable liquid and vapor



Physical state liquid

Odor Aromatic Petroleum distillates

Precautionary Statements - Prevention

Appearance viscous

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection Avoid breathing dust/fume/gas/mist/vapors/spray Use only outdoors or in a well-ventilated area Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment Use explosion-proof electrical/ ventilating/ lighting/ equipment Use only non-sparking tools Take precautionary measures against static discharge

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention If skin irritation occurs: Get medical advice/attention IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower Wash contaminated clothing before reuse IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician if you feel unwell In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed Store locked up Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful if swallowed. May be harmful in contact with skin. Very toxic to aquatic life with long lasting effects. Very toxic to aquatic life.

Unknown acute toxicity

46.0661914% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable

Mixture

Chemical Name	CAS No	Weight-%
Xylenes (o-, m-, p- isomers) *	1330-20-7	10 - 30

KL310AS - KOP-R-LASTIC ALUMINUMSTON

Hydrocarbon resins *	Proprietary	10 - 30
Limestone *	1317-65-3	10 - 30
Rubber compounds *	Proprietary	10 - 30
Paraffin oils *	8012-95-1	7 - 13
Silica, amorphous, fumed, crystalline-free *	112945-52-5	1 - 5
Titanium dioxide *	13463-67-7	0.1 - 1

*The exact percentage (concentration) of composition has been withheld as a trade secret.

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

Description of first aid measures

General advice	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). If symptoms persist, call a physician.	
Eye contact	Keep eye wide open while rinsing. Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. If symptoms persist, call a physician.	
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician. Wash contaminated clothing before reuse.	
Inhalation	Remove to fresh air. If breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If symptoms persist, call a physician.	
Ingestion	Call a physician or poison control center immediately. Do not induce vomiting without medical advice. Rinse mouth. Never give anything by mouth to an unconscious person.	
Self-protection of the first aider	Remove all sources of ignition. Use personal protective equipment as required.	
Most important symptoms and effe	cts, both acute and delayed	
Symptoms	May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Drowsiness.	
Indication of any immediate medical attention and special treatment needed		
Note to physicians	Keep victim warm and quiet.	
5. FIRE-FIGHTING MEASURES		

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical, CO2, sand, earth, water spray or regular foam.

Unsuitable extinguishing media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors. Vapors form explosive mixtures with air: indoors, outdoors, and sewers explosion hazards.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Stop leak if you can do it without risk.
Other Information	Water spray may reduce vapor; but may not prevent ignition in closed spaces.
Environmental precautions	
Environmental precautions	Prevent entry into waterways, sewers, basements or confined areas.
Methods and material for containm	nent and cleaning up
Methods for containment	A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.
Methods for cleaning up	Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill for later disposal.
	7. HANDLING AND STORAGE
Precautions for safe handling	
Advice on safe handling	Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray.
Conditions for safe storage, includ	ling any incompatibilities
Storage Conditions	Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place.
Incompatible materials	Strong oxidizing agents. Strong acids. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Xylenes (o-, m-, p- isomers)	STEL: 150 ppm	TWA: 100 ppm	-
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³	
Limestone	-	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m ³ total dust
1317-65-3		TWA: 5 mg/m ³ respirable fraction	TWA: 5 mg/m ³ respirable dust
Paraffin oils	TWA: 5 mg/m ³ inhalable fraction	TWA: 5 mg/m ³	IDLH: 2500 mg/m ³
8012-95-1	excluding metal working fluids,		TWA: 5 mg/m ³
	highly & severely refined TWA: 5		STEL: 10 mg/m ³
	mg/m ³ inhalable fraction excluding metal working fluids		
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	IDLH: 5000 mg/m ³

NIOSH IDLH Immediately Dangerous to Life or Health

Appropriate engineering controls

Engineering Controls

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations	When using do not eat, drink or smoke. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Color	liquid viscous pigmented	Odor Odor threshold	Aromatic Petroleum distillates No information available
Property pH Melting point / freezing point Boiling point / boiling range Flash point Evaporation rate Flammability (solid, gas)	Values No information available No information available 150 °C / 302 °F 24 °C / 75 °F No information available No information available	Remarks • Method	Cup (PMCC)
Flammability Limit in Air Upper flammability limit: Lower flammability limit: Vapor pressure Vapor density Relative density Water solubility Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties	9% 1% No information available No information available 0.9 - 1.3 Insoluble in water No information available No information available No information available >100 mm2/s No information available No information available No information available	@ 40 °C	
Other Information Softening point Molecular weight VOC Content (%) Density Bulk density	No information available No information available No information available No information available No information available		

10. STABILITY AND REACTIVITY

Reactivity No data available

Chemical stability Stable under recommended storage conditions. Possibility of Hazardous Reactions None under normal processing. Conditions to avoid Heat, flames and sparks. Incompatible materials. Incompatible materials Strong oxidizing agents. Strong acids. Strong bases. Hazardous Decomposition Products Thermal decomposition can lead to release of irritating and toxic gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Irritating to eyes.
Skin contact	Irritating to skin.

Ingestion No data available.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Xylenes (o-, m-, p- isomers) 1330-20-7	= 3500 mg/kg (Rat)	> 1700 mg/kg (Rabbit)> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat)4 h = 5000 ppm (Rat)4 h
Paraffin oils 8012-95-1	> 24 g/kg (Rat)	-	= 2062 ppm (Rat)4 h
Silica, amorphous, fumed, crystalline-free 112945-52-5	= 3160 mg/kg (Rat)	-	-
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-

Information on toxicological effects

Symptoms

May cause redness and tearing of the eyes. Coughing and/ or wheezing. May cause skin irritation. Vapors may cause drowsiness and dizziness.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity Carcinogenicity No information available. No information available.

The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346. This note applies only to certain complex oil derived substances in Annex I. This product contains titanium dioxide which is classified as a possible carcinogen when present as respirable dust. This is not relevant for this product since it is a liquid. The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylenes (o-, m-, p- isomers) 1330-20-7	-	Group 3	-	-
Paraffin oils 8012-95-1	A2	Group 1 Group 3	-	Х
Silica, amorphous, fumed, crystalline-free 112945-52-5	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	Х

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

IARC (International Agency for Research on Cancer)

Not classifiable as a human carcinoge	n
Group 1 - Carcinogenic to Humans	
Group 2B - Possibly Carcinogenic to H	lumans
OSHA (Occupational Safety and He	alth Administration of the US Department of Labor)
X - Present	
Reproductive toxicity	No information available.
STOT - single exposure	Target Organs. Respiratory system. Central nervous system. Eyes. Skin.
STOT - repeated exposure	No information available.
Chronic toxicity	Avoid repeated exposure.
Target Organ Effects	Eyes, Respiratory system, Skin, lungs.
Aspiration hazard	No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	3,800.00 mg/kg
ATEmix (dermal)	2,681.90 mg/kg
ATEmix (inhalation-dust/mist)	2.36 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects

51.0626 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Persistence and degradability

Not readily biodegradable.

Bioaccumulation

Chemical Name	Partition coefficient
Xylenes (o-, m-, p- isomers)	3.15
1330-20-7	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

<u>Waste treatment methods</u> Disposal of wastes	This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).	
Contaminated packaging	Do not reuse container.	
US EPA Waste Number	D001	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
Xylenes (o-, m-, p- isomers)	Toxic
1330-20-7	Ignitable

14. TRANSPORT INFORMATION

DOT	
UN/ID no	
Proper shipping name	

UN1133 Adhesives

Hazard Class Packing Group Special Provisions Description Emergency Response Guide Number	3 III B1, B52, IB3, T2, TP1 UN1133, Adhesives, 3, III 128
TDG UN/ID no Proper shipping name Hazard Class Packing Group Description	UN1133 Adhesives 3 III UN1133, Adhesives, 3, III
IATA UN/ID no Proper shipping name Hazard Class Packing Group ERG Code Special Provisions Description	UN1133 Adhesives 3 III 3L A3 UN1133, Adhesives, 3, III
IMDG UN/ID no Proper shipping name Hazard Class Packing Group EmS-No Special Provisions Description	UN1133 Adhesives 3 III F-E, S-D 223, 955 UN1133, Adhesives, 3, III, (24°C c.c.)

15. REGULATORY INFORMATION

All components used in this product are on the TSCA Inventory and the Canadian DSL.

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Xylenes (o-, m-, p- isomers) - 1330-20-7	1.0

Physical and Chemical

Personal protection X

Properties -

SARA 311/312 Hazard Categories	
Acute health hazard	
Chronic Health Hazard	
Fire hazard	
Sudden release of pressure hazard	
Reactive Hazard	

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Yes No Yes No

No

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylenes (o-, m-, p- isomers) 1330-20-7	100 lb	-	-	Х
1330-20-7				

<u>CERCLA</u>

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylenes (o-, m-, p- isomers)	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Carbon black - 1333-86-4	Carcinogen
Quartz - 14808-60-7	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Xylenes (o-, m-, p- isomers) 1330-20-7	Х	X	Х
Limestone 1317-65-3	Х	X	Х
Paraffin oils 8012-95-1	Х	X	Х
Carbon black 1333-86-4	Х	X	Х
Quartz 14808-60-7	Х	X	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

Instability 0

Physical hazards 0

Flammability 3

Flammability 3

16-Dec-2015 16-Dec-2015

<u>NFPA</u>	Health hazards 2
HMIS	Health hazards 2
Issue Date Revision Date	16-De 16-De
Revision Note No information available	10 20
Disclaimer	

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination

with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet