

ClearPatch™

Clear Roof Sealant

Physical Properties

-Colour	Clear	-Application Temperature	Minimum 5°C
-Solids by Weight	62% (approx.)	-Chemical Resistance	Resists water, calcium chloride, salt, mild acid and alkaline solutions.
-Weight	0.95 kg/l (approx.)		
-Drying Time	@50% R.H. 20°C		
Touch Dry	2 hours		
Firm Dry	7 days		

Description

Bakor ClearPatch™ is a clear rubberized waterproof sealant designed for general use in roof repairs. **ClearPatch™** can be applied to dry or wet surfaces and under inclement weather conditions. Its consistency permits easy application even in cold weather. **Bakor ClearPatch™** will not slump or flow when applied on vertical surfaces.

Features

- Clear product allows for transparent or “invisible” repairs
- Excellent adhesion to shingles, concrete, concrete block, metal, galvanized metal, brick and wood
- Can be used on dry or wet surfaces

Uses

Used as a transparent repair sealant to seal cracks in roofing membranes, coat shingles, repair flashings, gutters, eavestroughs, copings, skylights, monitors and sign anchors.

Limitations

Do not use **Bakor ClearPatch™** over coal-tar pitch coatings. For ease of application during cold weather, condition material in warm temperature before using.

Preparation

Surfaces must be sound, clean, and free from dust, dirt, rust, grease, oil, fungi, mold or frost.

Application

Apply by knife or trowel. Can be applied to a wet or dry surface. When sealing joints, seams or cracks, press **Bakor ClearPatch™** into the area in need of repair to obtain deep penetration and then “crown up” to ensure water will not collect in the space.

Clean Up

Use mineral spirits.

Caution

Contains flammable solvents. Take suitable fire precautions. Do not allow smoking or welding in working area. Keep away from heat and open flame. Use in well ventilated areas. Keep containers covered when not in use. Harmful if swallowed.

<>