

Physical Property	Typical Value	Test Method
Appearance	Black fibrous paste	-
Application Temperature (ambient)	-6.6 °C to 49 °C (20 °F to 120 °F)	-
Consistency	Trowel grade	-
Flash Point	40.5 °C (105° F)	ASTM D3278
VOC Content (maximum)	275 g/l	-
Weight	1.01 to 1.13 kg/l (8.5 to 9.5 lbs./gal.)	-

Approvals and Certifications

- Meets or exceeds the performance requirements of CAN/CGSB-37.5

Description

Bakor[®] 810-20 is an economical grade, solvent type plastic cement composed of asphalt, fibers and fillers. It provides weather resistance and ease of application. It dries to a tough, water resistant sealer.

Features

- Smooth, easy-to-use, trowel application
- Excellent adhesion to many common roof surfaces

Usage

Use as a weatherproofing compound for seams, joints and cracks and for repairing roofs, flashings, vents, copings, drain pipes, eaves, skylights and parapet walls. Also used for cementing down loose shingle tabs.

Application

Surface Prep: Surfaces must be dry, sound, clean and free from rust, loose paint, dust, dirt and grease.

Apply: Apply by knife, trowel or gun. When sealing joints, seams or cracks, press **Bakor[®] 810-20** into the space to obtain deep penetration and then "crown up" to ensure water will not collect in the space. Avoid use where solvent odours may taint food or other susceptible products. For ease of application during cold weather, condition material in warm temperature before using.

Coverage

Approximately 0.28 m²/L (12 sq. ft. per gallon) applied at 3 mm (1/8") thick.

Clean-up

Clean tools with mineral spirits.

Packaging

20 kg, 10 kg, 3.78 L, 300 mL

Precautions

When transporting this product, be sure the container is secured and the lid is tight. Do not allow container to tumble as this may loosen the lid and allow leakage to occur.

Bakor® 810-20 Plastic Roof Cement

For more information, visit www.henry.com or for technical assistance call us at 800-486-1278. For more information on Henry's® product warranty and liability disclaimer please visit www.ca.henry.com/warranty. Refer to the Safety Data Sheet prior to using this product. The Safety Data Sheet is available at www.henry.com or by emailing Henry® Product Support at productsupport@henry.com or by calling 800-486-1278.

Henry and Bakor are registered trademarks of Henry Company.

The technical and application information herein is based on the present state of our best scientific and practical knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by law. The user is responsible for checking the suitability of products for their intended use. Henry® Company data sheets are updated on a regular basis; it is the user's responsibility to obtain and to confirm the most recent version. Information contained in this data sheet may change without notice.