

Physical Properties

Appearance Black aggregate mix	Flammability Non-combustible	Maximum VOS 0.83 lbs/gal
Color Black	Flash Point 77°C (170°F)	Specific Gravity @ 25°C (77°F) 2.3
Drying Time @ 50% R.H. 20°C (68°F) Traffic immediately after compacting	Maximum VOC 50 g/l	Weight Per Gallon 11.1 - 11.5 lbs.

Description

BQ105 - B.K. AIRPORT GRADE POT HOLE FILLER is a ready-to-use asphalt and aggregate compound for filling pot-holes and cracks in asphalt paved driveways, parking areas, and pathways. It is convenient, quick setting, and compacts to a smooth, long lasting patch.

Features:

- Do-It-Yourself
- No special tools required
- Permanent
- No mixing necessary
- Instant repair
- All weather - hot or cold, wet or dry

Coverage

Approximately 4 sq. ft. x 1 in. deep

Surface Preparation

FOR USE ON EXTERIOR ASPHALT SURFACES ONLY.

Material should be room temperature or higher just prior to use. DO NOT HEAT CONTAINER. Brush away any loose debris or standing water. Remove any weeds and kill roots with weed killer.

Application

STEP 1: Remove loose debris from the hole. Remove any water from the hole.

STEP 2: Apply Pot-Hole Filler with a trowel or shovel. Fill hole in 5 cm (2") layers.

STEP 3: Press down repaired area with a trowel or shovel. Compact with tamper or similar device to fully compact. You cannot over-compact. If patch seems soft, it needs more compaction.

Wise Tips: Wait 90 days before applying driveway sealer. Can be applied in any temperature. To accelerate hardening and prevent tracking, dust compacted surface with sand or cement.

Precautions

For best results, material should be at room temperature or higher just prior to use. **DO NOT HEAT CONTAINER.** When transporting this product, be sure the pail is secured and the lid is tight. Do not allow container to tumble, as this may loosen the lid and allow leakage to occur.

Cleanup

Tools may be cleaned with mineral spirits. Care should be used in handling solvents.

Caution

CAUTION! COMBUSTIBLE! Contains petroleum distillate. Keep away from heat and flame. Do not heat container or store at temperatures greater than 110°F. **CLOSE AIR INTAKES** until solvents dissipate. Contains volatile solvents that might contaminate potable water. Close container after each use. Dispose of container and unused contents in accordance with Local, State and Federal regulations. **DANGER! HARMFUL OR FATAL IF SWALLOWED.** If swallowed, do not induce vomiting. **CALL PHYSICIAN IMMEDIATELY!** Use protective measures to avoid contact with eyes and skin. In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least 15 minutes. **GET MEDICAL ATTENTION!**

USE ONLY WITH ADEQUATE VENTILATION! Avoid breathing of vapor. If you experience eye water, headaches or dizziness, leave area or increase fresh air or wear respirator (NIOSH/MSHA TC 23C or equal). Repeated and prolonged occupational overexposure to solvent vapor may cause permanent brain and nervous system damage, and may cause liver or kidney damage.

KEEP OUT OF REACH OF CHILDREN.

Employers should obtain a copy of the **Material Safety Data Sheet (MSDS)** from your supplier or directly from Henry at the toll free number or website below.

Product Sizes

6KG (15 lb)

20KG (45 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective that substantially affect performance within 12 months of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.** This limited warranty is in addition to and supplemented by the product warranty located on our website at: www.ca.henry.com/warranty which also applies to this product.