

Physical Properties

Appearance Black liquid	Drying Time @ 50% R.H. 68°F (20°C) Dry to touch in 4 hours	Solids By Weight 42 - 46%
Application Temperature 50°F (10°C) and rising	Flash Point >212 °F (100°C)	Specific Gravity @ 77° F (25°C) 1.14 - 1.20
Brookfield Viscosity 5000-7500 cPs	Freezability Do not freeze	Weight Per Gallon 9.5 - 10.0 lbs
Color Black brown	Maximum VOC 50 g/l	

Description

Features:

- Rubberized for long life
- Penetrates and seals asphalt surfaces
- Fast curing formula

Coverage

23 to 38 sq. m (250-400 sq. ft.) per 17.0 L pail. Coverage may vary according to surface age, porosity, weather conditions and application method.

Surface Preparation

Clean loose debris from pavement with broom and rinse with a garden hose. Remove grease and oil with **Airport Grade™ Multi-Purpose Driveway Cleaner** or detergent. Treat chemical spills with **Airport Grade™ Oil Spot Primer**. On hot days, dampen surface before application. Sweep away puddles.

Repair all cracks and holes and allow to cure thoroughly. For cracks up to 6 mm (1/4"), use **Airport Grade™ Asphalt Driveway Crack Filler** or **Airport Grade™ Depression Filler**. For cracks up to 12 mm (1/2") use **Airport Grade™ Depression Filler**. Over 12 mm (1/2"), use **Airport Grade™ Pot-Hole Filler**.

Application

Mix thoroughly using wooden paddle and apply undiluted with the brush side of a squeegee in 3-4 foot sections using a cross pattern to coat evenly. Smooth out ridges and excess sealer. Apply early in the day for more curing time. Product cures to a rich black color. Apply in a single, even coat. Multiple coats or applying too thickly will cause slow curing and cracking. Cures to touch in 4 hours. Normally driveable in 24 - 48 hours.

Precautions

Do not use on concrete or asphalt less than six months old. Do not mix with coal tar pitch or asphalt/solvent-based sealer. Do not dilute. Do not apply if rain or temperatures below 10°C (50°F) are forecast within 48 hours. When transporting this product, be sure the pail is secured and the lid is tight to prevent spills.

Cleanup

Clean uncured sealer with water. For cured sealer, use biodegradable terpene solvent.

Caution

CAUTION! Close container after each use. **DO NOT TAKE INTERNALLY!** Use protective measures to avoid contact with eyes and skin. If swallowed, **CALL PHYSICIAN IMMEDIATELY!** In case of eye contact, open eyelids wide and flush immediately with plenty of water for at least fifteen minutes. **GET MEDICAL ATTENTION!** Dispose of container and unused contents in accordance with Local, Provincial and Federal regulations.

KEEP OUT OF REACH OF CHILDREN!

KEEP FROM FREEZING.

FOR EXTERIOR USE ONLY.

Employers should obtain a copy of the **Material Safety Data Sheety (MSDS)** from your supplier or directly from the toll free number or website below.

Product Sizes

17L (43 lb)

Limited Warranty

We, the manufacturer, warrant only that this product is free of defects, since many factors which affect the results obtained from this product - such as weather, workmanship, equipment utilized and prior condition of the substrate - are all beyond our control. We will replace at no charge any product proved to be defective within 2 years of purchase, provided it has been applied in accordance with our written directions for uses we recommended as suitable for this product. Proof of purchase must be provided. **DISCLAIMER OF WARRANTIES AND LIMITATION OF LIABILITY: THIS LIMITED WARRANTY IS IN LIEU OF ANY OTHER WARRANTIES EXPRESS OR IMPLIED INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FOR A PARTICULAR PURPOSE. MANUFACTURER SHALL HAVE NO LIABILITY OF ANY KIND BEYOND PRODUCT REPLACEMENT, INCLUDING FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES RESULTING FROM ANY DEFECTS OR ANY DELAYS CAUSED BY REPLACEMENT OR OTHERWISE. THIS LIMITED WARRANTY PROVIDES THE PURCHASER'S EXCLUSIVE REMEDY FOR ANY DEFECT IN THE PRODUCT.**