

### Surface Preparation

Chisel crack open to minimum 3/4" wide by 3/4" deep, to create a greater surface area for bonding with cement. Always undercut or cut square and do not use a V shaped cut. Clean all loose material from crack or hole.

### Application

**Mixing:** Place a small amount of **SN222 - S.M. INSTANT WATERSTOP** in mixing pail. Add water, and mix into a putty-like consistency. Using a trowel or hand, form cement into a cone shape. Beginning at the top, force cement firmly into crack. Where rushing water is present, force cement in crack and hold in place until set.

### Caution

Do not swallow. Do not get product in eyes. Do not get on skin or clothing. Causes burns. Wear safety glasses, protective clothing and dust mask. Do not breathe fumes. Use only in well ventilated area. Handle with care. Contains cement. When wet, forms a calcium hydroxide solution. If swallowed, call a poison control center or doctor immediately. Do not induce vomiting. If product gets into eyes, rinse with water for at least 15 minutes. If product gets on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

**KEEP OUT OF REACH OF CHILDREN.**

### Product Sizes

4.5KG (10 lb)

### Limited Warranty

The consumers shall satisfy themselves of the suitability of this product for the intended purpose. Weather, applicator's skill and surface conditions are beyond manufacturer's control. We, therefore, limit our liability to replacement of defective material only, within one year of proof of purchase