

## Description

**SN225 - INSTANT PATCH CEMENT** is an exceptionally strong, fast-setting, low slump mortar for use on concrete and masonry. Ideal for exterior and interior steps, walls, driveways, vertical and overhead trowel applied patching without using formwork. Ready for light traffic in an hour. Can be used from feather edge to 2" in one layer.

## Surface Preparation

Remove all cracked, spalled and deteriorated concrete to create a solid surface. Remove loose concrete and rust using a wire brush. Wash the area clean with water. Remove standing water and leave surface damp before applying product. Mix only what may be applied in ten minutes. Prepare "mixing liquid" by combining 1 part **Stone Mason ACRYLI BOND** to 3 parts water. In a clean mixing container, place mixing liquid and slowly add **SN225 - INSTANT PATCH CEMENT**. Mix to a putty like consistency. Do not over mix. Add more mixing liquid if necessary. Discard all material that has set before it can be placed. Clean out the mixing container between batches. For 10 lb. **SN225 - INSTANT PATCH CEMENT** you need approximately 16 fl. oz. mixing liquid.

## Application

Brush apply a coat of freshly mixed mortar to the properly prepared and prewetted surface, scrubbing the mortar vigorously into the surface. Immediately apply fresh mortar to the still wet brush coat with firm trowel pressure. Apply in layers of 1" for vertical surfaces and 2" for horizontal surfaces.

**Limitations:** Do not apply when temperatures are below 40°F or when rain is forecasted within 24 hours. Do not apply over control or expansion joints. Do not apply in immersed areas unless a waterproof protective topcoat is applied.

For a stronger bond, use **Stone Mason ACRYLI BOND** mixed 1:3 ratio with water as the mixing liquid instead of plain water. Mix **SN225 - INSTANT PATCH CEMENT** with straight **Acryli Bond** into a brushable consistency and brush onto the dampened area to be patched. While still wet, apply **SN225 - INSTANT PATCH CEMENT** mixed to a putty like consistency. For superior curing and protection, seal patched area with **Stone Mason CONCRETE SEALER**.

## Product Sizes

4.5KG (10 lb)

## Limited Warranty

The consumers shall satisfy themselves of the suitability of this product for the intended purpose. Weather, applicator's skill and surface conditions are beyond manufacturer's control. We, therefore, limit our liability to replacement of defective material only, within one year of proof of purchase