

Description

SN234 - S.M. FLOOR PATCH/LEVELER & SKIM CT CMNT is a premium, high performance, fast setting, polymer modified portland cement based floor patch, leveling and skim coat cement. Properly mixed and applied, it will not shrink or crack. Can be applied from feather edge to 12 mm (1/2") thick and has superior compressive and abrasive strength.

READ ALL DIRECTIONS FIRST BEFORE PROCEEDING.

Usage

SN234 - S.M. FLOOR PATCH/LEVELER & SKIM CT CMNT is used to provide smooth and level finish on interior subfloors prior to the installation of floor coverings. Use as a patch to fill cracks, seams and holes; use as a leveler to level uneven and rough surfaces or as a skim coat on concrete, plywood, ceramic tile, stone, terrazzo, marble and sheet vinyl and fully cured residual cutback surfaces. It can be used for above and below grade applications.

Coverage

Approximately 4.6 sq. m (50 sq. ft.) applied at 1.5 mm (1/16") thickness or 1.1 sq. m (12 sq. ft.) applied at 6 mm (1/4") thickness.

Surface Preparation

Surfaces must be structurally sound prior to application of **SN234 - S.M. FLOOR PATCH/LEVELER & SKIM CT CMNT**. Secure loose boards or tiles with screws, nails and/or recommended adhesive. Substrates must be clean and free from dirt, grease, oil, wax, sealers, mildew, soap film and all loose material. Loose, scaly paint shall be scarified. Concrete must be fully cured and not subject to hydrostatic pressure.

MIXING: Mix only sufficient material for use within 10 minutes. Always use clean water, containers and tools. Use a ratio of 1 part cold water to 3 parts powder and mix to a smooth, creamy consistency. Apply immediately. For greater adhesion, performance and for applications over cutback adhesives, sheet vinyl, terrazzo, ceramic tile and plywood, use **Stone Mason ACRYLI BOND** in place of water. Avoid excessive mixing and warm water as this will shorten working and hardening time of new mix. Always add powder to liquid when mixing. Avoid using high speed mixing to prevent air entrainment (should not exceed 300 rpm). Mix by hand or by electric drill and paddle for larger mixes. **WORKING TIME:** 10 minutes

Application

Test a small area first to determine suitability. Apply with a putty knife or flat cement finishing trowel. Once dry, sand any surface imperfections to obtain required smoothness.

Set Time: Initial set is approximately 25-30 minutes and the material will dry within 1-2 hours depending on the applied thickness, temperature and humidity conditions. Once completely dry, installation of new flooring material can commence.

Limitations: FOR INTERIOR USE ONLY. Do not apply directly over gypsum based substrates. **SN234 - S.M. FLOOR PATCH/LEVELER & SKIM CT CMNT** is not designed to be a final floor surface and must be overlaid with a suitable floor covering before exposed to traffic. Work in dry climate, at temperatures between 10°C (50°F) and 38°C (100°F). If a level area over 1.5 m (5 ft.) in diameter is required, use **EZ FLOW** or **SUPER E-Z FLOW FLOOR UNDERLAYMENT**.

Cleanup

Clean tools and hands with clean water before material sets.

Caution

Contains cement. When wet, forms a calcium hydroxide solution. Do not swallow. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. Do not get in eyes. If in eyes, rinse with water for at least 15 minutes. Do not get on

skin or clothing. If on skin, rinse well with water. If product gets on clothes, remove clothes. Causes burns. Do not breathe fumes. If product is breathed in, remove person to fresh air. Handle with care. Wear safety glasses, protective clothing and dust mask. Use only in well-ventilated area.

KEEP OUT OF REACH OF CHILDREN.

Product Sizes

4.5KG (11 lb)	11.3KG (26 lb)
---------------	----------------

Limited Warranty

The consumers shall satisfy themselves of the suitability of this product for the intended purpose. Weather, applicator's skill and surface conditions are beyond manufacturer's control. We, therefore, limit our liability to replacement of defective material only, within one year of proof of purchase