



- NOTES:**
1. DETAIL SHOWS **BLUESKIN® VP160** ASSEMBLY INSTALLED OVER EXTERIOR GRADE GYPSUM SHEATHING. OTHER ACCEPTABLE SUBSTRATES INCLUDE PLYWOOD, OSB, CONCRETE, AND CONCRETE BLOCK.
 2. PRIME RAW EDGES OF EXTERIOR GYPSUM SHEATHING WHERE **AIR-BLOC® LF** IS ANTICIPATED TO LAP ONTO CUT AND EXPOSED GYPSUM CORE AT PIPE PENETRATION HOLE. RECOMMENDED PRIMER/ADHESIVE INCLUDE: **BLUESKIN® SPRAY PREP**.
 3. REFER TO **BLUESKIN® VP160** INSTALLATION GUIDELINES FOR RECOMMENDED INSTALLATION PROCEDURES.

Henry®

15 Wallsend Drive,
Scarborough, Ontario, M1E 3X6
800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

BLUESKIN® VP160 SELF-ADHERED WATER RESISTIVE AIR BARRIER

PIPE PENETRATION

SUBSTRATE GAPS UP TO 12 mm WIDE GAP MAXIMUM
AIR-BLOC® LF LIQUID-APPLIED FLASHING

SCALE: N.T.S.

09-29-2016

BSVP160 - 2B