

- DETAIL SHOWS BLUESKIN® VP160 ASSEMBLY INSTALLED OVER EXTERIOR GRADE GYPSUM SHEATHING. OTHER ACCEPTABLE SUBSTRATES INCLUDE PLYWOOD, OSB, CONCRETE, AND CONCRETE BLOCK.
- 2. INSTALL FLASHING AT SILL PAN EXTENDING 152 mm MINIMUM UP JAMB.
- 3. WINDOW INSTALLATION REQUIREMENTS TO BE VERIFIED BY DESIGN PROFESSIONAL.
- PRIME BLUESKIN® VP160 WHERE SELF-ADHERED FLASHING LAPS ONTO BLUESKIN® VP160 WHEN ENHANCED SEAM ADHESION IS DESIRED. RECOMMENDED PRIMERS/ADHESIVES INCLUDE: BLUESKIN[®] LVC ADHESIVE, AQUATAC™ PRIMER, HI-TAC[™] PRIMER, OR BLUESKIN[®] ADHESIVE.

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY, HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

REFER TO BLUESKIN® VP160 INSTALLATION GUIDELINES FOR RECOMMENDED INSTALLATION PROCEDURES.



15 Wallsend Drive,

Scarborough, Ontario, M1E 3X6

800-486-1278 • www.henry.com

BLUESKIN® VP160 SELF-ADHERED WATER RESISTIVE AIR BARRIER

REBATE WINDOW

SELF-ADHERED OR LIQUID APPLIED **FLASHING**

SCALE: N.T.S. 09-29-2016

BSVP160 - 6A