



NOTES:

1. DETAIL SHOWS HENRY® 790-11/790-11EV REINFORCED HOT RUBBERIZED ASPHALT WATERPROOFING ASSEMBLY FIELD MEMBRANE TRANSITION WITH HENRY® PUMADEC™ FLEX 31MV OR PUMADEC™ FLEX 30SL.
2. RECOMMENDED HENRY® ADHESIVE/PRIMER FOR 790-11/790-11EV INCLUDE: 910-01 ASPHALT PRIMER OR 930-18 POLYMER MODIFIED ADHESIVE. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET TO CONFIRM VOC COMPLIANCE.
3. FOR LONG-TERM COLOUR STABILITY: REFER TO DETAIL PUMADEC-SD2 FOR PUMADEC™ SYSTEM WITH HENRY® DEQCOAT™ TOP COAT.
4. PREPARE AND PRIME SUBSTRATES A MINIMUM 50 mm BEYOND PUMADEC™ SYSTEM APPLICATION IN ACCORDANCE WITH HENRY® PUMADEC™ SYSTEM SUBSTRATE PREPARATION GUIDELINES.
5. HENRY® OFFERS PAVERS, RIGID INSULATION, AND/OR PREFABRICATED DRAINAGE COMPOSITES AS A SINGLE SOURCE WARRANTY OPTION PER PROJECT SPECIFIC REQUIREMENTS. CONTACT HENRY® FOR SYSTEM CONFIGURATIONS AND WARRANTY OPTIONS.
6. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR AUTHORIZED SUBSTRATES.
7. REFER TO PRODUCT SPECIFIC GUIDE SPECIFICATION FOR RECOMMENDED INSTALLATION PROCEDURES.

Henry®

15 Wallsend Drive
 Scarborough, Ontario, Canada, M1E 3X6
 800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

PUMADEC™ FLEX 31MV OR FLEX 30SL TRANSITION - HENRY® 790-11

SYSTEM TRANSITION

**790-11/790-11EV WITH PUMADEC™ SYSTEM
 PMR, IRMA, PLAZA DECKS AND TERRACES - OPTION 2**

SCALE: N.T.S.

04-17-2018

PUMADEC-A2