



NOTES:

1. DETAIL SHOWS **HENRY® 790-11, 790-11EV** OR **CM100** WITH **HENRY® PUMADEC™ FLEX 31MV** FLASHING.
2. REFER TO PRODUCT SPECIFIC TDS FOR FIELD MEMBRANE ASSEMBLY COMPONENTS.
3. PRIMER FOR **790-11/790-11EV** NOT SHOWN FOR CLARITY. RECOMMENDED **HENRY®** ADHESIVE/PRIMER FOR **790-11/790-11EV** INCLUDE: **910-01 ASPHALT PRIMER** OR **930-18 POLYMER MODIFIED ADHESIVE**. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET TO CONFIRM VOC COMPLIANCE.
4. FOR LONG-TERM COLOUR STABILITY: REFER TO DETAIL PUMADEC-SD2 FOR **PUMADEC™** SYSTEM WITH **HENRY® DEQCOAT™** TOP COAT.
5. PREPARE AND PRIME SUBSTRATES A MINIMUM 50 mm BEYOND **PUMADEC™** SYSTEM APPLICATION IN ACCORDANCE WITH **HENRY® PUMADEC™** SYSTEM SUBSTRATE PREPARATION GUIDELINES.
6. REFER TO **PUMADEC™** SYSTEM TRANSITION DETAILS FOR PRODUCT SPECIFIC TRANSITION REQUIREMENTS.
7. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR AUTHORIZED SUBSTRATES.
8. REFER TO PRODUCT SPECIFIC GUIDE SPECIFICATION FOR RECOMMENDED INSTALLATION PROCEDURES.

Henry®

15 Wallsend Drive
Scarborough, Ontario, Canada, M1E 3X6
800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

PUMADEC™ FLEX 31MV FLASHING

CURB FLASHING

790-11/790-11EV/CM100 WITH **PUMADEC™** SYSTEM
FLASHING FOR UPTURN FLASHING AT CURB - OPTION 2

SCALE: N.T.S.

04-17-2018

PUMADEC-C5B