



NOTES:

1. DETAIL SHOWS HENRY® 790-11, 790-11EV OR CM100 FIELD MEMBRANE WITH HENRY® PUMADEC™ FLEX 31MV OR PUMADEC™ FLEX 30SL FLASHING.
2. REFER TO PRODUCT SPECIFIC TDS FOR FIELD MEMBRANE ASSEMBLY COMPONENTS.
3. PRIMER FOR 790-11/790-11EV NOT SHOWN FOR CLARITY. RECOMMENDED HENRY® ADHESIVE/PRIMER FOR 790-11/790-11EV INCLUDE: 910-01 ASPHALT PRIMER OR 930-18 POLYMER MODIFIED ADHESIVE. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET TO CONFIRM VOC COMPLIANCE.
4. PREPARE AND PRIME SUBSTRATES A MINIMUM 50 mm BEYOND PUMADEC™ SYSTEM APPLICATION IN ACCORDANCE WITH HENRY® PUMADEC™ SYSTEM SUBSTRATE PREPARATION GUIDELINES.
5. REFER TO REFER TO PUMADEC™ SYSTEM TRANSITION DETAILS FOR PRODUCT SPECIFIC TRANSITION REQUIREMENTS.
6. SUBSTRATE SHOWN IS FOR REFERENCE ONLY. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR AUTHORIZED SUBSTRATES.
7. REFER TO PRODUCT SPECIFIC GUIDE SPECIFICATION FOR RECOMMENDED INSTALLATION PROCEDURES.

Henry®

15 Wallsend Drive
 Scarborough, Ontario, Canada, M1E 3X6
 800-486-1278 • www.henry.com

MANUFACTURER GUIDE DETAILS ARE FOR REFERENCE ONLY. HENRY® DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING. PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION.

PUMADEC™ FLEX 31MV OR PUMADEC™ FLEX 30SL FLASHING

ROOF DRAIN

790-11/790-11EV/CM100 WITH PUMADEC™ SYSTEM FLASHING AT A ROOF DRAIN DETAIL - OPTION 2

SCALE: N.T.S.

04-17-2018

PUMADEC-D2E