

CREATE CONVEX LOOP IN MEMBRANE BY LOOPING INTO GAP, PRIOR TO INSTALLATION, ADHERE MEMBRANE TO ITSELF AND **INSTALL TO PREVENT** ADHESION TO BACKER ROD.





BLUESKIN VP100

HENRY SELF-ADHERED **FLASHING** (SEE GAP FLASHING DETAIL)

FLASHING INSTALLED BEFORE WRB

GREATER THAN 1" (25MM) UP TO 2" (50M) **PLAN VIEW** 3" (75MM) **BLUESKIN VP100** HENRY SELF-ADHERED FLASHING (SEE GAP FLASHING DETAIL)

FLASHING INSTALLED AFTER WRB

PLAN VIEW



HENRY 1-2-3 MOISTURE CONTROL SYSTEM WEATHER-RESISTIVE BARRIER (WRB) INSTALLATION GUIDELINES

NOTES

- 1. VISIT WWW.HENRY.COM/WARRANTY FOR ELIGIBILITY REQUIREMENTS OF THE 15-YEAR RESIDENTIAL AND LIGHT COMMERCIAL HENRY 1-2-3 MOISTURE CONTROL SYSTEM WARRANTY.
- 2. HENRY OFFERS BLUESKIN VP100 IN THE UNITED STATES AND CANADA. PRODUCT AVAILABILITY AND WARRANTY OPTIONS MAY VARY BY LOCATION. REFER TO THE HENRY BLUESKIN VP100 GUIDE SPECIFICATION FOR RECOMMENDED FLASHINGS. SEALANTS, AND SYSTEM INFORMATION.
- 3. SEE PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR ROLL SIZES, MAXIMUM UV EXPOSURE, COMPATIBILITY CONCERNS, APPLICATION TEMPERATURES AND SERVICE TEMPERATURE LIMITATIONS.
- 4. CLADDING, INSULATION, AND OPTIONAL INTERIOR VAPOR BARRIER NOT SHOWN FOR CLARITY, REFER TO LOCAL CODE ORDINANCES FOR INSULATION AND VAPOR BARRIER REQUIREMENTS.
- SUBSTRATES MUST BE CLEAN AND DRY.
- 6. SELF-ADHERED MEMBRANES MAY REQUIRE A PRIMER FOR OPTIMAL ADHESION TO SOME SURFACES AND/OR SUBSTRATE TEMPERATURES. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR PRIMER REQUIREMENTS.
- 7. ROLL SELF-ADHERED MEMBRANES TO OBTAIN CONTINUOUS ADHESION.
- 8. VERIFY WEATHER-RESISTIVE BARRIER IS FREE FROM PROTRUSIONS OR DAMAGE PRIOR TO CLADDING INSTALLATION.
- 9. CONTACT HENRY AT 800-773-4777 FOR TECHNICAL ASSISTANCE.



999 N. Pacific Coast Highway, Suite 800 El Segundo, CA 90245 800-486-1278 www.henry.com

BLUESKIN VP100 SELF-ADHERED AIR BARRIER NON-MOVING JOINTS

SUBSTRATE GAPS UP TO 2" (50MM) WIDE MAXIMUM SELF-ADHERED FLASHING

DOES NOT ASSUME RESPONSIBILITY FOR ERRORS OR DEVIATIONS IN DESIGN OR ENGINEERING, PROJECT SPECIFIC VERIFICATION IS RECOMMENDED PRIOR TO INSTALLATION. DETAILS ARE NOT TO SCALE. REFER TO PRODUCT SPECIFIC TECHNICAL DATA SHEET FOR PRODUCT INFORMATION, RECOMMENDED AUXILIARY COMPONENTS AND INSTALLATION INSTRUCTIONS.

11-05-2021

PAGE 1 OF 1

VPWRB-8C